



DSI 632
Double Twist Stranding Machine



DSI 632

Design:

- foundation-free installation on vibration damping elements
- prepared for application of shielding with Al-laminated polyester film

Increase in quality:

- maximum production reliability and production quality (overturn monitoring, wire break sensors and length measurement in the spool carrier, monitoring of the bearing temperature)
- designed for the production of pairs, quads and cable bundles to the highest quality standards and for the twisting of bundles and data cables

Increase in productivity:

- good accessibility in the spool carrier for easy insertion of the product

Energy and cost efficiency:

- user-friendly operation through infinitely variable adjustment of the production parameters at the control panel (number of twists, lay length, twist diameter, traverse width correction)
- all drives feature three-phase AC drive technology and digital technology,

offering precise synchronization and reduced maintenance by virtue of contactless data transfer

- use of a single bow system for reduced energy consumption and reduced noise emission

Technical data

max. production speed		m/min	300
		fpm	985
production range	lay length, infinitely variable	mm	6 ... 180
	max. no. of twists, infinitely variable	twists/min	5,600
spool dimensions	max. spool flange dia.	mm	630
	total length	mm	475
max. stranding dia.	standard machine	mm	6.0
	reinforced execution	mm	8.5
single wire dia.	solid	AWG	30 ... 18
	flexible	AWG	25 ... 15
drive for	rotor bow		standard AC motor
	winding spool		AC servo motor
max. sound pressure level		dBA	80
	(acc. to EN ISO 3743-2 and DIN 45635-1)		
machine dimensions (W x D x H)		m	3.10 x 1.81 x 1.85
weight		kg	approx. 3,500